

UTILITY

Attorney Docket No.

1999-0507

Total Pages

32

PATENT APPLICATION
TRANSMITTAL

First Named Inventor or Application Identifier

Balachander Krishnamurthy et al.

Express Mail Label No.

EL354902338US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, D.C. 20231

1. ☒ Fee Transmittal Form
(submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages 15]
(preferred arrangement set forth below)
- Descriptive title of invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R&D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings(if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s)(35 USC 113) [Total Sheets 6]
4. Oath or Declaration [Total Pages 3]
- a. ☒ Newly executed (original or copy)
- b. ☐ Copy from a prior application(37 CFR 1.63(d))
(for continuation/divisional with Box 15 completed)
[Note Box 15 below]
- i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s)
named in the prior application, see 37 CFR
1.63(d)(2) and 1.33(b)

5. ☐ Microfiche Computer Program (Appendix)
6. ☐ Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy(identical to computer copy)
- c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☒ Assignment Papers(cover sheet & document(s))
8. ☐ 37 CFR 3.73(b)Statement ☐ Power of Attorney
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure ☐ Copies of IDS
Statement(IDS)/PTO-1449 Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
14. ☐ Other :

15. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior Application No:

Prior application information: Examiner:

Group/Art Unit:

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

16. CORRESPONDENCE ADDRESS


☐ Customer Number or Bar Code Label

(Insert Customer No. or Attach bar code label here)

or ☒ Correspondence address below

NAME	Samuel H. Dworesky				
ADDRESS	AT&T CORP. P.O. Box 4110				
CITY	Middletown	STATE	New Jersey	ZIP CODE	07748-4110
COUNTRY	United States of America			FAX	732-368-6932

17. SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED

NAME	Cedric G DeLaCruz	Reg. #	36498
TELEPHONE	973-360-8122		
SIGNATURE		DATE	06/23/2000


"Express Mail" Mailing Label Number EL354902338US

Date of Deposit 06/23/2000

I hereby certify that this application is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington D.C. , 20231

Nancy C. Marcovici

(Printed Name of Person Mailing Paper)


(Signature of Person Mailing Paper)

METHOD FOR NETWORK-AWARE CLUSTERING OF CLIENTS IN A NETWORK

5 This application claims the benefit of United States provisional application
No. 60/151,194, filed August 27, 1999 and titled SYSTEM AND METHOD FOR NETWORK-
AWARE CLUSTERING OF WEB CLIENTS/PROXIES.

BACKGROUND OF THE INVENTION

10 This invention relates to a method of grouping or clustering clients within a network to
optimize and expedite the flow of data within the network.

15 Servers, such as proxy servers, cache servers, content distribution servers, mirror servers
and other related servers are typically used to speed the access of data and reduce response time
for network client requests in a network, such as the World Wide Web. Generally, these network
clients issue requests for information, such as in the form of a Hypertext Transfer Protocol
(HTTP) requests for some information, such as one or more Web pages. These requests are then
20 handled directly or indirectly by these servers, such as proxy servers, caches servers, content
distribution servers and mirror servers, to hopefully expedite the accessing and transfer of the
requested information.

25 Generally, these servers either act as intermediaries or as transfer or redirection points for
client requests in the network. For example, in operation, a proxy server receives a request for
an Internet service (such as a Web page request) from a user. If the request passes filtering
requirements, the proxy server looks in its local cache of previously downloaded Web pages. If
the server finds the page, the page is returned to the user without needing to forward the request
to, for example, a World Wide Web server on the Internet. If the page is not in the cache, the
proxy server, acting as a client on behalf of the user, requests the page from the server out on the
30 Internet. When the page is returned, the proxy server relates it to the original request and
forwards it on to the client user.

Strategically designing placement of proxies in the network can benefit greatly from clustering network client users who are from the same network together so that the proxy server can adequately and efficiently serve these respective client clusters. Mis-characterizing clients as being in the same network may result in a proxy server being placed such that it impracticably and inefficiently serves these clients resulting in degraded performance in the network.

In the case of, for example, a cache or a content distribution server, the user's HTTP request at an originating server is typically re-routed away from the originating server and on to a cache server "closer" to the user. Generally, the cache server determines what content in the request exists in the cache, serves that content, and retrieves any non-cached content from the originating server. Any new content may also be cached locally in the cache server.

Similar to the strategic placement of proxies, the placement of cache servers, content distribution "boxes" or servers and related mirror servers can be best made by accurately clustering clients together in the network. Performance in the network may thus be improved by accurately and properly clustering multiple network clients together in related client clusters. The servers, whether they are cache servers, content distribution servers and/or mirror servers can then efficiently service these client clusters.

Accordingly, it would be desirable to have a method for accurately clustering clients within a network together to guide placement of proxies, cache servers, content distribution servers and mirror servers within the network.

SUMMARY OF THE INVENTION

The present invention is a method for guiding placement of servers, such as proxy servers, cache servers, content distribution servers and mirror servers within a distributed information network. The method uses information from at least one network log, such as a server log or proxy log, and at least one network routing table to arrange clients into related client clusters. In one embodiment, the method includes the steps of generating a unified prefix/netmask table from a plurality of extracted prefix/netmask entries, extracting a plurality of client IP addresses from the at least one network log, comparing each of the plurality of client IP addresses with entries in the unified/prefix netmask table to determine a common longest matching prefix between each of the plurality of client IP addresses and the entries in the unified/prefix netmask table and grouping all of the client IP addresses which share the common longest matching prefix into at least one client cluster. Each client within a client cluster will share a common network address prefix from the unified routing table with the other clients in the same client cluster.

Preferably, a number of different routing table snapshots are used in extracting entries for the unified prefix/netmask table. These multiple entries from the different prefix/netmask tables are unified into a singular format and then merged into a single table.

Network servers, such as proxy servers, cache servers, content distribution servers and mirror servers may be assigned to one or more clusters based on a number of factors such as the number of clients within the cluster, the number of requests issued, the URLs accessed and the number of bytes fetched from a server, such as a Web server.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates an exemplary network configuration in accordance with the teachings of the present invention.

5

FIG. 2 illustrates an exemplary method in accordance with the teachings of the present invention.

FIG. 3 illustrates an exemplary routing table containing routing information.

10

FIG. 4 illustrates an exemplary method for creating a unified routing table in accordance with the teachings of the present invention.

FIG. 5 illustrates an exemplary table containing routing information and unified routing information.

15

FIG. 6 illustrates an exemplary method for clustering clients in accordance with the teachings of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

United States provisional application No. 60/151,194, titled SYSTEM AND METHOD FOR NETWORK-AWARE CLUSTERING OF WEB CLIENTS/PROXIES filed August 27, 1999 is hereby incorporated by reference herein in its entirety.

The present invention relates to a method for clustering clients and allocating servers, such as proxy servers, cache servers, content distribution servers and mirror servers, to those client clusters in a distributed information network, such as the World Wide Web. Referring to FIG. 1, an exemplary network 10 configured in accordance with the teachings of the present invention is shown. The network 10 includes a number of clients, such as clients 20 (C1, C2....Cn) which are clustered together in a client cluster 30, clients 40 (CA1, CA2, CA3CAN) which are clustered together in a client cluster 50 and clients 60 (CB1, CB2....CBn) which are clustered together in a client cluster 70. Client cluster 30 is in communication with servers 32, 34 which together form a server cluster 36, client cluster 50 is in communication with servers 52, 54 and 56 which form a server cluster 58 and client cluster 70 is in communication with a single server 72. In the present invention, servers 32, 34, 52, 54, 56 and 72 may be any one of proxy servers, cache servers, content distribution servers and/or mirror servers. For example, server 32 and server 34 may be proxy servers such that server cluster 36 is a proxy server cluster.

Server cluster 36 including servers 32 and 34, server cluster 58 including servers 54, 56 and 58 and server 72 are in further communication with a server, such as a World Wide Web server 90. World Wide Web server may be any server available on the Internet which is responsive to requests to and from any one of the clients and/or servers. For example, World Wide Web server may be a server which receives and responds to requests for Web pages related to one or more Web sites which are resident on the server. Other network configurations are possible provided the network servers, such as the network proxy servers, cache servers, content distribution servers and mirror servers are allocated to properly clustered client clusters as discussed in more detail later herein.

In the present invention, the placement and configuration of the servers and server clusters, such as the proxy servers and related proxy server clusters, cache servers and related cache server clusters, content distribution servers and content distribution server clusters and mirror servers and related mirror server clusters depends on the clustering of clients within the network. For example, using a content caching scheme for illustrative purposes, a client may issue a request for content, such as HTTP request to a World Wide Web server. This may be performed by the Web client clicking on a URL that is “content-delivery enabled”, i.e. the URL includes the use of a special routing code that redirects the Web page request to the optimum or “closest” server. This “content-delivery enabled” URL will re-route that client’s request away from the site’s originating Web server and on to a cache server or cache server cluster, that is better suited to serve the client.

Referring to FIG. 2, an exemplary embodiment of a method for clustering clients and assigning or allocating servers to these client clusters is shown. In this embodiment, a unified routing information table is created, step 110. The unified routing information table, preferably includes routing information from one or more routing tables, such as network routing prefix and netmask information. For background purposes, a netmask is a series of bits designed to “mask” or conceal certain portions of an IP address. Typically, the standard netmask for a class C network like is 255.255.255.0 where the “255.255.255” prefix portion identifies the network number and the last octet, “.0”, is the actual machine number or subnetwork number. Referring again to FIG. 2, clients within the network are classified into client clusters based on information from the unified routing information table, step 120. Servers, such as proxy servers, cache servers, network distribution servers and mirror servers may then be assigned to these client clusters, step 130, as discussed in more detail later herein.

As shown in FIG. 2, the present invention utilizes routing table information from, preferably, two or more routing tables to create a unified routing information table. For background purposes, a router is a device or, in some cases, software in a computer, that determines the next network point to which a packet should be forwarded toward its destination. The router decides which way to send each information packet based on its current understanding of the state of the networks it is connected to. Typically, routers create or

maintain a routing table of the available routes and their conditions and uses this information along with distance and cost algorithms to determine the best route for a given packet. An exemplary routing table or routing table “snapshot” 160 is shown in FIG. 3. As shown, the routing table or routing table snapshot 160 may include information such network prefix and netmask information 170, network identification information 180 and AS path information 190. Other additional information such as next hop IP address and AS number, etc may also be available via the network routing table. In an exemplary embodiment, as discussed above, information from a plurality of routing tables are used to create the unified routing table for use in clustering clients together.

Referring to FIG. 4, an exemplary method for creating a unified routing table is shown. To create the unified table, a number of prefix/netmask entries are extracted from a number of routing tables or routing table snapshots, step 200. Although only a single routing table or routing table snapshot may be used, preferably two or more routing tables or routing table snapshots are used since any one table is unlikely to contain the desired information on all the necessary prefix/netmask entries. Each router in a network such as the World Wide Web will typically only see a limited set of traffic, thereby it is desirable to use a multiplicity of different routing tables from different routers in order to obtain a more complete set of routing information. The prefix/netmask entries from the various tables are unified into a single standardized format, step 210, as discussed in more detail later herein. The standardized prefix/netmask entries are then merged into a single unified table, step 220, to aid in clustering together clients in the network. Typically, the unified routing table will be created periodically to incorporate possibly updated information from the routing tables in the network. The unified routing table may be created or generated at any interval such as every two hours, once a month or ten times a year as desired.

Referring to FIG. 5, a network prefix/netmask entry may be in one of three formats as shown in a tabular form. A first exemplary format 230 is configured generally as $x1.x2.x3.x4/k1.k2.k3.k4$ and is used in exemplary routing tables MAE-EAST, MAE-WEST, PACBELL AND PAIX, where $x1.x2.x3.x4/k1.k2.k3.k4$ are network prefix and netmask respectively with zeroes dropped at the end or tail. One such example is 193.1/255.255, which

corresponds to 193.1.0.0/255.255.0.0, where 193.1.0.0 and 255.255.0.0 are network prefix and netmask, respectively.

Referring again to FIG. 5, another exemplary network prefix/netmask entry format 240 may also be configured as x1.x2.x3.x4/l as in routing tables at ARIN, AT&T, CANET, NLANR AND VBNS, where x1.x2.x3.x4 is the prefix and l is the netmask length. For example, 128.148.0.0/16 stands for 128.148.0.0/255.255.0.0, where 128.148.0.0 and 255.255.0.0 are network prefix and netmask. Additionally, another exemplary prefix/netmask entry format may be configured as x1.x2.x3.0 which can also be found in CANET, and is an abbreviated representation of x1.x2.x3.0/k1.k2.k3.0. For example, 130.15.0.0 is an abbreviated representation of 130.15.0.0/255.255.0.0. Of course, other formats may exist and may be utilized herein provided the different formats are standardized to a singular format to aid in clustering clients in the network.

In the present invention, the network prefix/netmask entries are unified into a single standardized format as previously discussed herein and shown as step 210 in FIG. 4. Any one of the formats as discussed above or other network prefix/netmask formats that may exist will preferably be converted into this single standardized format. In one exemplary embodiment, the format x1.x2.x3.x4/k1.k2.k3.k4 is chosen as the standardized format. For instance, any network prefix/netmask entries in the format of x1.x2.x3.x4/l and/or the format x1.x2.x3.0 will be converted into the format x1.x2.x3.x4/k1.k2.k3.k4 such that prefix/netmask entries 128.148.0.0/16, 130.15.0.0 and 192.75.72.0 will be converted respectively into 128.148/255.255, 130.15/255.255 and 192.75.72/255.255.255. These converted prefix/netmask entries are then tabulated into a single unified table with prefix/netmask entries existing in all the same format. This table may be in a simple tabular form with the multiple prefix/netmask entries listed in a grid array form.

Referring now to FIG. 6, an exemplary method for clustering clients using the unified prefix/netmask table is shown. A number of client IP addresses are first extracted from a network server log, step 300. The server log may be any generally available server log, such as a World Wide Web server log which collects client request information to the Web server. The

extracted client IP addresses are matched with the entries in the unified prefix/netmask table to determine a common network address prefix, step 310. Such matching may be performed by conducting a longest prefix matching on each client IP address with each of the entries in the unified prefix/netmask table. Once prefix matching has been performed, the client IP addresses are clustered into respective client clusters, step 320. In each respective client cluster, each of the clients within a client cluster will share a common prefix, or more specifically, a common longest matching prefix from the unified prefix/netmask table. A threshold for prefix matching may be set such that a client IP address has to have at least a certain number of matching digits in the client IP address prefix with any one of the prefix/netmask entries in the unified prefix/netmask table before a match is declared. For example, in one embodiment, a client IP address may have to prefix match at least four digits of any one of the prefix/netmask entries in the unified prefix/netmask table to be considered a match.

Once clients have been clustered together in client clusters as discussed above, servers, such as proxy servers, cache servers, content distribution servers and/or mirror servers may be placed or assigned to these client clusters. Preferably, in the case of proxy servers, the proxy servers being assigned to these client clusters will be functioning as cache servers and thereby their optimum assignment or placement will depend greatly on the proper clustering of these clients. In the present invention, the servers may be assigned to these client clusters based on one or more factors or metrics such as the number of clients, the number of requests issued, the URLs accessed, the number of bytes fetched from a server and other related factors. In one embodiment, more than one server, such as a proxy server, cache server, content distribution server and/or mirror server may be assigned to the same client cluster or clusters such that the servers will together form a server cluster, as discussed earlier herein. The servers within a server cluster will act in concert with one another to service their respective client cluster(s).

In one example, proxy servers, cache servers, content distribution servers and/or mirror servers may be assigned to a client cluster based simply on the number of clients in the respective client cluster. For example, a client number threshold may be set such that a server may be assigned for every instance of the client number threshold reached. A threshold may be set at any number such as 100, 500 or a 1000 clients. In an exemplary embodiment, where the

client number threshold is set at 500, a client cluster containing 4000 clients will require and be assigned at least eight (8) servers, whether they may be proxy servers, cache servers, content distribution servers and/or mirror servers. These eight servers together will form a server cluster which will be placed in front of the client cluster in the network to service the clients requests to and from the Internet.

In another example, proxy servers, cache servers and/or content distribution servers may be assigned to one or more client clusters based on the number of requests, such as HTTP request, which are issued by the clients within each respective client cluster. For example, a request threshold may be set such that a server may be assigned for client clusters which issue a certain number of requests which equals or exceeds the threshold. A threshold may be set at any number depending on the anticipated capacity of the server to be assigned to the client cluster.

In another exemplary embodiment, at least one server, such as a proxy server, cache server, content distribution server and/or mirror server, may be placed in front of each client cluster. The servers may be further grouped into server clusters based on their respective AS numbers and respective geographical locations. In this example, all servers belonging to the same AS and located geographically nearby will be grouped together to form a server cluster. In addition, in some instances, undesirable network spiders and conflicting proxy servers are eliminated from a client cluster before placing a server, such as a proxy server, cache server, content distribution server and/or mirror server to server that client cluster.

It will be apparent to those skilled in the art that many changes and substitutions can be made to the system and method described herein without departing from the spirit and scope of the invention as defined by the appended claims.

We claim:

1 1. A method of clustering a plurality of client IP addresses within a distributed information
2 network, the method comprising the steps of:

3 generating a unified prefix/netmask table from a plurality of network routing table
4 prefix/netmask entries;

5 comparing each of the plurality of client IP addresses with the unified prefix/netmask
6 table to determine a common prefix between each of the plurality of client IP addresses and at
7 least one of the entries in the unified prefix/netmask table; and

8 grouping client IP addresses which share a common prefix into a network client cluster.

1 2. The method of claim 1, wherein the step of generating a unified prefix/netmask table
2 from a plurality of network routing table prefix/netmask entries includes the steps of:

3 extracting the prefix/netmask entries from a plurality of network routing tables; and
4 converting the prefix/netmask entries into a standardized format.

1 3. The method of claim 1, wherein the client IP addresses are extracted from a network log.

1 4. The method of claim 3, further comprising:
2 identifying existing spiders and/or proxies within the network log.

1 5. The method of claim 1, further comprising:
2 placing one or more servers in front of a network client cluster, wherein the servers are at
3 least one of proxy servers, cache servers, content distribution servers and mirror servers.

1 6. The method of claim 1, wherein the common prefix is the common longest matching
2 prefix from the unified prefix/netmask table.

1 7. The method of claim 1, wherein the distributed information network is the World Wide
2 Web.

1 8. A method for guiding placement of servers within a distributed information network
2 using at least one network server log and at least one network routing table from the distributed
3 information network, the method comprising:

4 extracting a plurality of prefix/netmask entries from the at least one network routing
5 table;

6 generating a unified prefix/netmask table from the plurality of extracted prefix/netmask
7 entries;

8 extracting a plurality of client IP addresses from the at least one network server log;

9 comparing each of the plurality of client IP addresses with entries in the unified/prefix
10 netmask table to determine a common longest matching prefix between each of the plurality of
11 client IP addresses and the entries in the unified/prefix netmask table; and

12 grouping all of the client IP addresses which share the common longest matching prefix
13 into at least one client cluster.

1 9. The method of claim 8, wherein generating a unified prefix/netmask table from the
2 plurality of extracted prefix/netmask entries includes:

3 converting the prefix/netmask entries into a standardized format.

1 10. The method of claim 8, wherein the servers are selected from the group consisting of
2 proxy servers, cache servers, content distribution servers and mirror servers.

1 11. The method of claim 8, wherein each client cluster is assigned one or more servers.

1 12. The method of claim 8, further comprising:

2 assigning one or more servers to each client cluster based on the number of requests
3 issued by the clients within each client cluster.

ABSTRACT

A method for clustering together network clients for guiding of placement of network servers is disclosed. A number of routing table prefix/netmask entries are aggregated and unified into a tabular format. The routing table entries may be converted into a singular format. A network server log is used to extract a number of client IP addresses which are compared to the entries within the unified routing table. A common prefix shared by a number of the client IP addresses and an entry in the unified routing table is determined and used to cluster the clients together in a client cluster. Network servers, such as proxy server, cache servers, content distribution servers and mirror server may be placed in the network according to the client clusters.




FIG. 1







FIG. 2

160



Routes		AS path
134.87.2.0/24	BCnet	6509 271
134.117.0.0	Carleton University	6509 10786
137.82.0.0	University of British Columbia	6509 271
137.122.0.0	University of Ottawa	6509 10786


170


180



190

FIG. 3




FIG. 4

	230	240	250
Formats	x1.x2.x3.x4/k1.k2.k3.k4	x1.x2.x3.x4/l	x1.x2.x3.0
Routing Tables	MAE-EAST MAE-WEST PACBELL PAIX	ARIN AT&T CANET NLANR VBNS	CANET
Examples	193.1/255.255 193.0.128/255.255.192	128.148.0.0/16	130.15.0.0
Unification	193.1/255.255 193.0.128/255.255.192	128.148.0.0/255.255	130.15.0.0/255.255 192.75.72/255.255.255

FIG. 5




FIG. 6

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION	Attorney Docket Number	1999-0507
	First Named Inventor	Balachander Krishnamurthy
	COMPLETE IF KNOWN	
	Application Number	
	Filing Date	
	Group Art Unit	
<input checked="" type="checkbox"/> Declaration Submitted with Initial Filing <input type="checkbox"/> Declaration submitted after Initial Filing	Examiner Name	

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.
I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

Method For Network-Aware Clustering Of Clients In A Network

(Title of Invention)

the specification of which

☒ is attached hereto

OR

☐ was filed on _____ as United States Application Number or PCT International Application Number _____ and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37 Code of Federal Regulations, § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code § 119 (a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of an application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
			<input type="checkbox"/>	YES	NO
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) below.

Application Number(s)	Filing Date(MM/DD/YYYY)	
60/151,194	08/27/1999	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto

SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231

Attorney Docket Number: 1999-0507

DECLARATION - Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 C.F.R. 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT International application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) with full power of substitution and revocation, to prosecute this application, to make alterations and amendments therein, to receive the patent, and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number

Place Customer Number Bar
Code Label here

OR

☒ Registered practitioner(s) name/registration number listed below

Name	Registration Number	Name	Registration Number
CONOVER, Michele L.	34962	DELACRUZ, Cedric G	36498
DWORETSKY, Samuel H.	27873	STEINMETZ, Alfred G.	22971
ISAACSON, Thomas M.	44166	LEE, Benjamin S.	42787
LEVY, Robert B.	28234	MCGAHAN, Susan E.	35948
MONKA, Gary H.	35290	NAVON, Jeffrey M	32711

☒ I also appoint the following additional registered practitioner(s) named on the supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto with full power to prosecute said application, to make alterations and amendments therein, and to transact all business in the Patent and Trademark Office connected therewith.

Direct all Correspondence to:

☐ Customer Number or Bar Code Label

(Insert Customer No. or Attach bar code label here)

or ☒ Correspondence address below

NAME	Samuel H. Dworetsky				
ADDRESS	AT&T CORP. P.O. Box 4110				
CITY	Middletown	STATE	New Jersey	ZIP CODE	07748-4110
COUNTRY	United States of America			FAX	732-368-6932

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Name	Balachander Krishnamurthy		
Signature	[Signature]		Date 6/23/2000
Citizenship	United States		
Address (line 1)	60 East 8th Street, Apt. 5C		
Address (line 2)	New York		
Address (line 3)	New York County		
Address (line 4)	New York		
Address (line 5)	USA		
Zip Code	10003		

☒ Additional Inventors are being named on the 1 separately numbered sheets attached hereto

SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231

Attorney Docket Number: 1999-0507

DECLARATION**ADDITIONAL INVENTOR(S)**
Supplemental Sheet
Page of**Name of Additional Joint Inventor, if any:**☐ A petition has been filed for this unsigned inventor**Name** Jia Wang**Signature****Date**

6/23/2000

Citizenship

United States

Address (line 1)

30 Lake Street, Apt. 4A

Address (line 2)

White Plains

Address (line 3)

Westchester County

Address (line 4)

New York

Address (line 5)

USA

Zip Code

10603

Name of Additional Joint Inventor, if any:☐ A petition has been filed for this unsigned inventor**Name****Signature****Date****Citizenship****Address (line 1)****Address (line 2)****Address (line 3)****Address (line 4)****Address (line 5)****Zip Code****Name of Additional Joint Inventor, if any:**☐ A petition has been filed for this unsigned inventor**Name****Signature****Date****Citizenship****Address (line 1)****Address (line 2)****Address (line 3)****Address (line 4)****Address (line 5)****Zip Code****Name of Additional Joint Inventor, if any:**☐ A petition has been filed for this unsigned inventor**Name****Signature****Date****Citizenship****Address (line 1)****Address (line 2)****Address (line 3)****Address (line 4)****Address (line 5)****Zip Code**

SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231